



Connessione elettrica <i>Electrical connection</i>			NC WHITE OR BLUE NO BROWN
L = 500 mm fili/wires	P520F8 - 100	P520F8 - 500	
L = 1 mt cavetto/cable	P520F8 - 110	P520F8 - 510	
L = 2 mt cavetto/cable	P520F8 - 120	P520F8 - 510	

Per passare da N.C. a N.A. è sufficiente capovolgere il galleggiante

The contact can be converted from N.C. to N.O. by rotating the float upside down

Contatto SPDT - *SPDT Contact*

For correct fixing, we recommend using a burr-free 22 mm hole and a 2-5 mm thick wall.
When using non-insulated connections, the necessary precautions must be taken to ensure the minimum safety distance between the terminals.
For customized version (material, type of cable, temperature > 80°C, voltage > 50V, etc.) please contact Euroswitch.

Use	Mineral Oils - Diesel fuel - Petrol
Fixing	Expansion gasket
Stem	Nylon
Float	Nylon
Nut	Nylon
Expansion gasket	NBR (others on request)
Type of contact	Reed N.O./ N.C. (SPDT)
Max switch. capacity	40 W - (3 W SPDT)
Max switch. current	1 A - (0,25 A SPDT)
Max switch. voltage	50 V
Fluid specific weight	> 0,85
Working temperature	-10°C / +100°C
Weight	~ gr 24