



CODICE - PART NUMBER

Connessione elettrica Electrical connection		ORANGE OR BLACK	NC WHITE OR BLUE NO BROWN
L = 500 mm fili/wires	P535F8 - 100		P535F8 - 500
L = 1 mt cavetto/cable	P535F8 - 110		P535F8 - 510
L = 2 mt cavetto/cable	P535F8 - 120		P535F8 - 520
Per passare da N.C. a N.A. è sufficiente capovolgere il galleggiante The contact can be converted from N.C. to N.O. by rotating the float upside down		Contatto SPDT - SPDT Contact	

Nel caso di connessioni non isolate devono essere prese le adeguate precauzioni per garantire la distanza minima di sicurezza tra i diversi morsetti. Per versioni personalizzate (materiali, tipo di cablaggio, temperatura > 100°C, tensione > 50V, ecc.) contattare Euroswitch. Per un corretto impiego vedere le note generali del catalogo sensori Euroswitch, ultima edizione.

When using non-insulated connections, the necessary precautions must be taken to ensure the minimum safety distance between the terminals. For customized version (materials cable, different length, temperature > 100°C, voltage > 50V etc.) please contact our customer service. For a correct use please refer to "General Notes" in the Euroswitch sensors catalogue, last edition.

Impiego	Oli minerali - Gasolio
Fissaggio	G 1/2" conico
Stelo	Nylon
Galleggiante	Nylon
Tipo contatto	Reed N.A./ N.C. (SPDT)
Max potenza commut.	40 W (3 W SPDT)
Max corrente commut.	1 A (0,25 A SPDT)
Max tensione commut.	50 V
Peso specif. liquido	> 0,85
Temp. di funzionamento	-10°C / +100°C
Peso	~ gr 24

Use	Mineral oils - Diesel fuel
Fixing	G 1/2" conical
Stem	Nylon
Float	Nylon
Type of contact	Reed N.O./ N.C. (SPDT)
Max switch. capacity	40 W (3 W SPDT)
Max switch. current	1 A (0,25 A SPDT)
Max switch. voltage	50 V
Specific fluid weight	> 0,85
Working temperature	-10°C / +100°C
Weight	~ gr 24